



NOTES:

1. SIDEWALK IS 4" MINIMUM THICKNESS. SIDEWALK THROUGH DRIVEWAYS IS 5" MINIMUM THICKNESS, OR THE DRIVEWAY THICKNESS, WHICHEVER IS GREATER. SIDEWALKS THROUGH ALLEYS IS 7" MINIMUM THICKNESS.
2. 1/2" EXPANSION MATERIAL REQUIRED AT PROPERTY LINE AND DRIVEWAYS AND EACH 75 FT. INCREMENT ALONG LENGTH OF SIDEWALK.
3. TOLERANCE ON RIGHT-OF-WAY GRADING IS 0.5%. SUBJECT TO PROVIDING MINIMUM SLOPE TO AVOID PONDING WATER.
4. HORIZONTAL TOLERANCE IN SIDEWALK LOCATION IS $\pm 2"$ ON STRAIGHT AWAY AND $\pm 4"$ ON CURVES.

FILE NO.: 2700-112	CEDAR RAPIDS METROPOLITAN AREA STANDARD DETAILS FOR PUBLIC IMPROVEMENTS		NO. 2700-112
APPROVAL DATE: APRIL 2003			
REVISION NO.: 3	TYPICAL SIDEWALK AND RIGHT-OF-WAY GRADING		
REVISION DATE: FEB. 2015			

